TECHNICAL DATA SHEET



CLEAN EXTREME ACRYLIC EGGSHELL

Clean Extreme Acrylic Eggshell offers a finish that is 100% more stain resistant compared to conventional matt vinyl emulsion. It has superior cleaning capabilities which do not compromise the integrity or finished appearance of the paint film. New and aged stains can be easily cleaned away, returning walls to an 'as new' condition – reducing the need for costly redecoration. A subtle mid sheen finish that has been independently tested to ISO 11998 class 1 scrub rating for guaranteed results in high traffic areas.

AVAILABILITY

Colour Range White and pastel base, refer to current Crown Trade Literature

Packaging 5 litre.

PROPERTIES

Drying Time Under normal drying conditions touch dry in 1-2 hours and recoatable after 4 hours.

Allow for adequate ventilation during the drying period

Finish Mid sheen.

Composition Pigment: Titanium dioxide, coloured pigments and extenders.

Binder: Acrylic polymer.

Solvent: Water.

Spreading Rate Up to 14m² per litre on smooth surfaces.

Wet Film Thickness 71 micrometres at 14m² per litre

Dry Film Thickness 25 micrometres at 14m² per litre.

Volume Solids 35.5% White, other colours will vary.

Flash Point Not applicable

VOC Content EU limit value for this product (cat.A/b): 100 g/l (2010). This product contains max. 44g/l

VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall

below 8°C or when the relative humidity is above 80% during application or the drying

period.

PREPARATION

with the adhesion of the materials to be applied. Powdery surfaces should be primed with one coat of Sandtex Trade Water Based Stabilising Solution. Polished or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer or where a water-based alternative is required Crown Trade Grip Extreme. Porous surfaces should be coated with a 'mist' coat of Crown Trade Clean Extreme Durable Acrylic Eggshell diluted with 40% clean water by volume. Where clean water is not available, apply one coat of Crown Trade Covermatt Drywall Primer. Any areas of surface filling after priming should

be touched in with the priming or mist coat diluted as for main areas.

Previously Decorated Surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare, filled and powdery areas as for new surfaces above. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas are still contaminated with substances likely to cause staining and / or bleeding, patch prime with one coat of Crown Trade PSB Stain Block Primer.

COATING SYSTEM

Apply two coats as required. Certain colours may require additional coats to give complete obliteration.

APPLICATION

Stir well before use. Apply by brush or medium pile roller. For airless spray (dilution may be required. For further information follow the spray manufacturer's guidelines. Always intermix packs for colour consistency. Please check for colour accuracy prior to application. Crown Paints is not liable for decorating costs caused as a result of an incorrect colour being applied.

A small residue of colour may be wiped away when the painted surface is first cleaned. This is entirely normal and in no way compromises the integrity or finished appearance of the paint film. Marks on the painted surface can be wiped away with a damp cloth.

CLEANING

Return surplus material to container. Clean with a proprietary cleaner immediately after use. For further information contact the Crown Paints Customer Relations Team.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Do not store below 5°C or above 40°C. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0330 0240297 Fax: 0330 0240278

e-mail: <u>info@crowntrade.co.uk</u> website: <u>www.crowntrade.co.uk</u>

This information is correct at date of issue August 2017.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG Tel: 01254 704951 Fax: 01254 870155

Email: info@crowntrade.co.uk
Website: www.crowntrade.co.uk